

— Section 1 —  
Product Identification



# Material Safety Data Sheet

The Sherwin-Williams Co.  
101 Prospect Ave. N.W.  
Cleveland, OH 44115

Emergency telephone number  
Information telephone number  
Date of preparation

(216) 566-2917  
(216) 566-2902  
October 22, 2003

©2003, The Sherwin-Williams Co.

## ULTRA INTERIOR® System

## ACR-I

CAS No.	— Section 2 — Hazardous Ingredients (percent by weight)	ACGIH	OSHA	Units	LD50	LC50	Vapor Pressure mm Hg	Non-Lead	Lead-Containing
		TLV <STEL>	PEL <STEL>		(Rat-Oral) mg/kg	(Rat) ppm/4hr.		UIC-LF (Pb)	UIC-LL (Pb)
108-88-3	§ Toluene	50	100 <150>	ppm (skin)	5000	4000	22.0	6 - 13	6 - 13
100-41-4	§ Ethylbenzene	100 <125>	100 <125>	ppm	3500	NAv	7.1	1 - 3	1 - 3
1330-20-7	§ Xylene	100 <150>	100 <150>	ppm	4300	5000	5.9	8 - 15	8 - 15
78-83-1	§ 2-Methyl-1-propanol	50	50	ppm	2460	NAv	8.7	1 - 2	1 - 2
78-93-3	§ Methyl Ethyl Ketone	200 <300>	200 <300>	ppm	2740	NAv	70.0	36 - 46	36 - 46
110-43-0	Methyl n-Amyl Ketone	50	100	ppm	1670	NAv	2.1	0 - 5	0 - 5
123-86-4	n-Butyl Acetate	150 <200>	150 <200>	ppm	13100	2000	10.0	0 - 8	0 - 8
112-07-2	§ 2-Butoxyethyl Acetate	NAv	NAv		2400	NAv	1.0	1 - 2	1 - 2
14807-96-6	Talc	2	2	mg/m3 as Resp. Dust	NAv	NAv		5 - 10	5 - 10
Proprietary	Coated Mica	3	3	mg/m3 as Dust	NAv	NAv		0 - 3	0 - 3
13463-67-7	Titanium Dioxide	10	10[5]	mg/m3 as Dust [Resp. Fraction]	NAv	NAv		0 - 20	0 - 20
1333-86-4	Carbon Black	3.5	3.5	mg/m3	NAv	NAv		0 - 1	0 - 1
8007-18-9	Nickel Antimony Titanate	0.5	0.5	mg/m3	NAv	NAv		0 - 3	0 - 3
68186-90-3	Antimony Chromium Titanium Oxide	0.5	0.5	mg/m3	NAv	NAv		0 - 3	0 - 3
1344-37-2	Lead Chromate	0.05	0.05	mg/m3	NAv	NAv			<15
12656-85-8	Molybdate Orange								
	§ Chromium III [% Chromium] - maximum							3 [0.06]	3 [0.06]
	§ Chromium VI [% Chromium] - maximum								15 [2.2]
	§ Nickel [% Nickel] - maximum							3 [0.1]	3 [0.1]
	§ Antimony [% Antimony] - maximum							3 [0.3]	4 [0.4]
	§ Lead [% Lead] - maximum								15 [9.0]
	Weight per Gallon (lbs.)							7.8 - 9.0	7.8 - 9.0
	VOC (Volatile Organic Compounds) Emitted - lbs./gal.							5.3 - 5.9	5.3 - 5.9
	VOC Less Water & Federally Exempt Solvents - lbs./gal.							5.3 - 5.9	5.3 - 5.9
	Photochemically Reactive							Yes	Yes
	Flash Point (°F)							25 - 35	25 - 35
	HMIS (NFPA) Rating (health - flammability - reactivity) / PAINT SAFE® Personal Protection							2 - 3 - 0 / J3	2* - 3 - 0 / J3

P  
E  
R  
C  
E  
N  
T  
  
B  
Y  
  
W  
E  
I  
G  
H  
T

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

## Section 3 — Hazards Identification

**ROUTES OF EXPOSURE** - INHALATION of vapor or spray mist. EYE or SKIN contact with the product, vapor or spray mist.

### EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death. Certain colors contain Lead (see TABLE & PRODUCT LABEL). Acute occupational exposure to Lead is uncommon, but results in effects and symptoms similar to chronic overexposure described below.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE** - Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE** - None generally recognized.

**CANCER INFORMATION** - For complete discussion of toxicology data refer to Section 11.

## Section 4 — First Aid Measures

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

INGESTION: Do not induce vomiting. Get medical attention immediately.

## Section 5 — Fire Fighting Measures

**FLAMMABILITY CLASSIFICATION** - RED LABEL -- Flammable, Flash below 100 °F

**FLASH POINT** - See TABLE *LEL* 0.5 *UEL* 13.1

**EXTINGUISHING MEDIA** - Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS** - Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES** - Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure buildup & possible autoignition or explosion when exposed to extreme heat.

## Section 6 — Accidental Release Measures

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED** - Remove all sources of ignition.

Ventilate the area. Remove with inert absorbent.

## Section 7 — Handling and Storage

**DOL STORAGE CATEGORY** - 1B

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING** - CONTENTS ARE FLAMMABLE. Keep away from heat, sparks, and open flame. During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. Consult NFPA Code. Use approved Bonding and Grounding procedures. Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

## Section 8 — Exposure Controls/Personal Protection

**PRECAUTIONS TO BE TAKEN IN USE** - Certain colors contain Lead (see TABLE & PRODUCT LABEL). Before initial use of Lead-Containing colors (see TABLE), consult OSHA's Standard for Occupational Exposure to Lead (29 CFR 1910.1025).

Use all products only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg./m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg./m<sup>3</sup> (total dust), 5 mg./m<sup>3</sup> (respirable fraction).

**VENTILATION** - Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION** - If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding, wirebrushing, abrading, burning or welding the dried film, wear a particulate respirator approved by NIOSH/MSHA for protection against non-volatile materials in Section 2.

**PROTECTIVE GLOVES** - Wear gloves recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION** - Wear safety spectacles with unperforated sideshields.

**OTHER PRECAUTIONS** - These products may be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Certain colors contain Lead (see TABLE & PRODUCT LABEL). Do not apply Lead-containing colors on toys and other children's articles, furniture, or any interior surface of a dwelling or facility which may be occupied or used by children. Do not apply on any exterior surface of dwelling units, such as window sills, porches, stairs, or railings to which children may be commonly exposed.

## Section 9 — Physical and Chemical Properties

PRODUCT WEIGHT	7.8 - 9.0 lb/gal	EVAPORATION RATE	Slower than ether
SPECIFIC GRAVITY	0.96 - 1.08	VAPOR DENSITY	Heavier than air
BOILING POINT	174 - 184 °F	MELTING POINT	Not Available
VOLATILE VOLUME	75 - 85 %	SOLUBILITY IN WATER	N.A.

## Section 10 - Stability and Reactivity

STABILITY - Stable

CONDITIONS TO AVOID - None known.

INCOMPATIBILITY - None known.

HAZARDOUS DECOMPOSITION PRODUCTS - By fire: Carbon Dioxide & Monoxide, Oxides of Metals in Section 2

HAZARDOUS POLYMERIZATION - Will not occur

## Section 11 — Toxicological Information

**CHRONIC Health Hazards** - Certain colors contain Lead and Chromium VI (see TABLE & PRODUCT LABEL). Chronic overexposure to Lead may result in damage to the blood-forming, nervous, urinary, and reproductive systems (including embryotoxic effects). Symptoms include abdominal discomfort or pain, constipation, loss of appetite, metallic taste, nausea, insomnia, nervous irritability, weakness, muscle and joint pains, headache and dizziness. Chromates are listed by IARC and NTP. Although studies have associated exposure to Chromium VI compounds with an increased risk of respiratory cancer, available evidence indicates that Lead Chromate (Chrome Yellow, Molybdate Orange) DOES NOT present this hazard.

Ethylbenzene is classified by IARC as possibly carcinogenic to humans (2B) based on inadequate evidence in humans and sufficient evidence in laboratory animals. Lifetime inhalation exposure of rats and mice to high ethylbenzene concentrations resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. These effects were not observed in animals exposed to lower concentrations. There is no evidence that ethylbenzene causes cancer in humans.

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Limited evidence exists linking certain Nickel compounds to cancer in animals and possibly humans; however no direct evidence exists that Nickel Antimony Titanate is carcinogenic.

Methyl Ethyl Ketone may increase the nervous system effects of other solvents.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, blood forming, cardiovascular and reproductive systems.

Rats exposed to titanium dioxide dust at 250 mg./m<sup>3</sup> developed lung cancer, however, such exposure levels are not attainable in the workplace.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

## Section 12 — Ecological Information

No data available.

## Section 13 — Disposal Considerations

**WASTE DISPOSAL METHOD** - Waste from these products may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability and extractability to determine the applicable EPA hazardous waste numbers. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

## Section 14 — Transport Information

No data available.

## Section 15 — Regulatory Information

**CALIFORNIA PROPOSITION 65** - WARNING: These products contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA CERTIFICATION** - All chemicals in these products are listed, or exempt from listing, on the TSCA Inventory.

## Section 16 — Other Information

These products have been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.