



Material Safety Data Sheet

Western Automotive Finishes
101 Prospect Ave. N.W.
Cleveland, OH 44115

Emergency telephone number
Information telephone number
Date of preparation

(216) 566-2917
(216) 566-2902
October 8, 1999

©1999, Western Automotive Finishes

EXPRESS 3.5™ Acrylic System

ACR-V/W

— Section 2 — CAS No. Hazardous Ingredients (percent by weight)		ACGIH TLV <STEL>	OSHA PEL <STEL>	Units	Vapor Pressure (mm Hg)	3.5 Intermixes EXU - series Intermixed Colors	Activating Reducers W8870 3.5 Standard W8875 3.5 Slow W8876 3.5 Hot Weather			Clearcoat W8885 Integrating Clear
64742-48-9	V. M. & P. Naphtha.	300	300 <400>	PPM	12.0	19 - 25	38	23		28
64742-88-7	Mineral Spirits.	100	100	PPM	2.0	2 - 8	7	23	45	5
1330-20-7 §	Xylene.	100 <150>	100 <150>	PPM	5.9	1 - 2				2
64742-95-6	Light Aromatic Hydrocarbons.	Not Established			3.8		2	2	2	
108-67-8	1,3,5-Trimethylbenzene	25	25	PPM	10.0		3	3	3	
95-63-6 §	1,2,4-Trimethylbenzene	25	25	PPM	2.0		4	4	4	
110-43-0	Methyl n-Amyl Ketone.	50	100	PPM	2.1					
123-86-4	n-Butyl Acetate.	150 <200>	150 <200>	PPM	10.0		5	5	6	
108-65-6	1-Methoxy-2-Propanol Acetate	Not Established			1.8	0 - 10				
Unknown	Isophorone Diisocyanate Polymer.	Not Established					38	38	39	
4098-71-9	Isophorone Diisocyanate Monomer	0.005	0.005 <0.02>	PPM			0.3	0.4	0.3	
13463-67-7	Titanium Dioxide.	10	10[5]	Mg/M3 [Resp. as Dust Fraction]		0 - 25				
1333-86-4	Carbon Black	3.5	3.5	Mg/M3		0 - 2				
Weight per Gallon (lbs.)						8.0 - 9.0	7.41	7.45	7.52	8.04
VOC - Total Volatile Organic Compounds (lbs./gal.)						2.8 - 2.9	4.58	4.60	4.59	2.87
VOC - Less Water and exempt Solvents (lbs./gal.)						2.8 - 2.9	4.58	4.60	4.59	2.87
Photochemically Reactive						No	Yes	Yes	Yes	No
Flash Point (°F)						73	57	57	57	60
DOL Storage Category						1C	1B	1B	1B	1B
HMIS (NFPA) Rating (health - flammability - reactivity)						2* - 3 - 0	3* - 3 - 0	3* - 3 - 0	3* - 3 - 0	2 - 3 - 0

P
E
R
C
E
N
T

B
Y

W
E
I
G
H
T

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

Section 3 — Physical Data

<i>PRODUCT WEIGHT</i>	See TABLE	<i>EVAPORATION RATE</i>	Slower than Ether
<i>SPECIFIC GRAVITY</i>	0.93-1.2	<i>VAPOR DENSITY</i>	Heavier than Air
<i>BOILING RANGE</i>	240-419 °F	<i>MELTING POINT</i>	N.A.
<i>VOLATILE VOLUME</i>	35-71 %	<i>SOLUBILITY IN WATER</i>	N.A.

Section 4 — Fire And Explosion Hazard Data

FLAMMABILITY CLASSIFICATION *FLASH POINT* See TABLE *LEL* 0.7 *UEL* 13.1

RED LABEL - Flammable, Flash below 100 °F

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 5 — Health Hazard Data

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

EXPRESS 3.5™ Activating Reducers may cause allergic respiratory and/or skin reaction in susceptible persons or sensitization. This effect may be delayed several hours after exposure.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If any breathing problems occur during use, LEAVE THE AREA and get fresh air. If problems remain or occur later, IMMEDIATELY get medical attention.

If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and laundry before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED: Get medical attention.

CHRONIC Health Hazards

No ingredient in these products is an IARC, NTP, or OSHA listed carcinogen.

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, blood forming and reproductive systems.

Persons sensitive to isocyanates will experience increased allergic reaction on repeated exposure to isocyanates in EXPRESS 3.5™ Activating Reducers.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Section 6 — Reactivity Data

STABILITY -- Stable

INCOMPATIBILITY

Contamination of EXPRESS 3.5™ Activating Reducers with Water, Alcohols, Amines, and other compounds which react with isocyanates, may result in dangerous pressure in, and possible bursting of, closed containers.

CONDITIONS TO AVOID -- None known.

HAZARDOUS DECOMPOSITION PRODUCTS -- By fire: Carbon Dioxide, Carbon Monoxide, Oxides of Nitrogen, possibility of Hydrogen Cyanide

HAZARDOUS POLYMERIZATION -- Will Not Occur

Section 7 — Spill Or Leak Procedures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

If EXPRESS 3.5™ Activating Reducers are spilled, all personnel in the area should be protected as in Section 8. Cover spill with absorbent material. Deactivate spilled material with a 10% ammonium hydroxide solution (household ammonia). After 10 minutes, collect in open containers and add more ammonia. Cover loosely. Wash spill area with soap and water.

WASTE DISPOSAL METHOD

Waste from these products may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section 8 — Protection Information

PRECAUTIONS TO BE TAKEN IN USE

NO PERSON SHOULD USE THESE PRODUCTS, OR BE IN THE AREA WHERE THESE PRODUCTS ARE BEING USED, IF THEY HAVE CHRONIC (LONG-TERM) LUNG OR BREATHING PROBLEMS OR IF THEY EVER HAD A REACTION TO ISOCYANATES.

Use all products only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m3 (total dust), 3 mg./m3 (respirable fraction), OSHA PEL 15 mg./m3 (total dust), 5 mg./m3 (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

Where overspray is present, a positive pressure air supplied respirator (T1C19C NIOSH/MSHA approved) should be worn. If unavailable, a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II may be effective. Follow respirator manufacturer's directions for use. Wear the respirator for the whole time of spraying and until all vapors and mists are gone. NO PERSONS SHOULD BE ALLOWED IN THE AREA WHERE THESE PRODUCTS IS BEING USED UNLESS EQUIPPED WITH THE SAME RESPIRATOR PROTECTION RECOMMENDED FOR THE PAINTERS.

When sanding or abrading the dried film, wear a particulate respirator approved by NIOSH/MSHA for protection against non-volatile materials in Section II.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PROTECTIVE EQUIPMENT

Use barrier cream on exposed skin when using EXPRESS 3.5™ Activating Reducers.

Section 9 — Precautions

DOL STORAGE CATEGORY -- See TABLE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Contents are FLAMMABLE. Keep away from heat, sparks, and open flame.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

These products may be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section 10 — Other Regulatory Information

CALIFORNIA PROPOSITION 65

WARNING: These products contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the products. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.